



SITE PLAN AESTHETIC DESIGN CRITERIA

Please fill out the following in COMPLETE DETAIL, a restatement does not satisfy code requirements.

AESTHETIC DESIGN CRITERIA (Section 13-37)	
1.	<p><i>Harmonious and efficient organizations.</i> The site plan shall be organized harmoniously and efficiently in relation to topography, the size and type of plot, the character of adjoining property, and the type and size of buildings. The site will be developed to facilitate orderly development of surrounding property.</p> <p>Site is against Turnpike wall and in area away from units and will not impact the village or adjacent properties.</p>
2.	<p><i>Preservation of natural state.</i> Desirable vegetation or other unique natural features shall be preserved in their natural state when practical. Tree and soil removal and filling of natural watercourses shall be minimized.</p> <p>No natural vegetation will be disturbed. Area of modification will be landscaped.</p>
3.	<p><i>Enhancement of residential privacy.</i> The site plan shall provide reasonable visual and sound privacy for all adjacent dwelling units. Fences, walks, barriers and vegetation shall be arranged for protection and privacy.</p> <p>No residential structures are involved in modification and existing structures to remain, addition is on opposite side of units.</p>
4.	<p><i>Emergency access.</i> Structures and other site features shall be arranged to permit practical emergency vehicle access to all sides of buildings.</p> <p>All structures are accessible. The Turnpike wall is on the north side of the site with adequate access to the rear side.</p>
5.	<p><i>Access to public ways.</i> Every structure and dwelling unit shall have access to a public street, walkway or other area dedicated to common use.</p> <p>NW 59 Place connects to a public roadway</p>
6.	<p><i>Pedestrian circulation.</i> A pedestrian circulation system shall be provided which is separate from the vehicular circulation system.</p> <p>Sidewalks exist leading to the building.</p>
7.	<p><i>Design of access and egress drives.</i> The location, size, and numbers of ingress and egress drives to a site will be designed to minimize the negative impacts on public and private streets and on adjacent property.</p> <p>There is only one street in the project and there is no thru traffic.</p>
8.	<p><i>Coordination with off-site vehicular and pedestrian circulation systems.</i> The arrangement of rights-of-way or easements for vehicular and pedestrian circulation shall coordinate the pattern of existing and planned streets and pedestrian or bicycle pathways in the area.</p> <p>There is no off-site circulation issues, existing conditions to remain.</p>
9.	<p><i>Stormwater control.</i> Protective measures shall ensure that removal of stormwater runoff will not adversely affect neighboring properties or the public storm drainage system. Provisions shall be made for construction of wastewater facilities including grading, gutters, and piping to direct stormwater and prevent erosion. Surface water on all paved areas shall be collected at intervals which do not obstruct vehicular or pedestrian traffic.</p> <p>Stormwater will be contained on site, no roadway work is required and existing utilities are adequate for the minimal modification.</p>
10.	<p><i>Exterior lighting.</i> Location, type, size and direction of exterior lighting shall not glare or direct illumination which interferes with adjacent properties or safety of public rights-of-way.</p> <p>Lighting is existing and residential in nature with no interference with adjacent properties. No additional street lights are proposed.</p>
11.	<p><i>Protection of property values.</i> Elements of a site plan shall be arranged to have minimum negative impact on values of adjoining property.</p> <p>Modification is adjacent to turnpike on north and buffered by the county environmental area from adjacent residential on the south.</p>

M.S. ARCHITECTS, INC.
901 S. FEDERAL HIGHWAY #200
FORT LAUDERDALE, FL 33316
LIC. NO. AA C001695 • AR 7456
954.463.3096

December 10, 2020

GREEN BUILDING CONSTRUCTION STATEMENT

Planning Department
City of Coconut Creek

Re: Addition to Administrative Offices for
SOS Children's Villages
3681 NW 59 Place, Coconut Creek, Florida
Job No. 19-08-77

In accordance with Section 13-320 of the City of Coconut Creek's code, which recognizes that green building construction improves the efficiency with which sites utilize energy, water, and building materials to reduce development impacts on the environment and the city, all new development or redevelopment applications shall address the green building components detailed in Section 13-320(b) at time of development application submittal.

More precise details for the building will be included in the site plan submittal. The following are the guiding components that will be included:

I. Conservation of Natural Resources

A. Sustainable Site Development

1. Construction Pollution Prevention - An erosion and sedimentation control plan will be developed and implemented to control erosion and air born dust.
2. Construction Site Materials Recycling - Utilizing construction waste management practices 75% of the project's construction waste will recovered, reused and recycled. A regional waste management hauler shall be hired to haul, separate, sort and document all construction waste.

B. Minimize Disruption of Existing Plants and Trees

1. Native soil will be protected in areas not affected by the new construction.
2. Existing plants will be protected during construction and relocated, if necessary, for the placement of the new addition.

C. Water Management

Storm water drainage system will incorporate a combination of swale and underground storage enhancing drainage sustainability.

D. Protect Water Quality

1. Landscape design will incorporate native plant species and Xeriscaping to reduce need for landscape irrigation.
2. Water Efficiency - Toilets, urinals, private lavatory faucets and shower heads shall be water sense labeled and/or meet/exceed the USGBC baseline consumption values (water closet 1.6 GPF, lavatory faucets (restroom) 0.5 GPM, kitchen faucet 2.2 GPM, shower head 2.5 GPM)

E. Building Materials

1. The use of pre-engineered wood trusses makes use of small dimension lumber and helps preserve old growth forests.
2. The use of metal studs for interior wall partitions instead of wood studs helps in the preservation of existing forests.
3. The use of cement tile roof will provide a 50%-75% longer lifespan than asphalt-based roofing systems.

F. Recycling of Demolished Waste

1. Recycling of Demolished Waste - The building will incorporate a high level of regional and recycled material. By utilizing construction waste management practices, the project will divert 75-80% of construction waste based on weight. A regional waste management hauler will be hired to haul, separate, sort and document all construction waste.
2. Building Re-Use - The existing buildings will remain. Only minor modifications are being implemented in order to connect to the new addition.

II. Energy Efficiency

A. Energy Performance - Building will be designed to meet the 2017 Florida Building Code and Florida energy code which is 20% above the national baseline.

B. Building

1. Use of high energy efficiency windows will reduce heat gain and the consumption of electricity.
2. Properly sealing and caulking all openings and joints will reduce heat gain and consumption of electricity.

C. Electrical and Air Conditioning

1. Use of efficient appliances and LED lights will reduce the consumption of electricity.
2. Installation of a tankless water heater will reduce consumption of electricity.
3. Use of high SEER/EER air conditioning system and non-HCF refrigerant will reduce consumption of electricity.
4. Use of duct mastic on all air conditioning duct joints will reduce conditioned air loss and consumption of electricity.

III. Indoor Air Quality

A. Materials


1. Use of low or no VOC paint and wood finishes will improve air quality.
2. Use of formaldehyde-free materials will improve air quality.

B. Air Filtration

We will install high efficiency particulate air (HEPA) filter.



Miguel F. Sanchez, President
M.S. Architects, Inc.
msarchms@aol.com



February 9, 2021

Department of Sustainable Development
City of Coconut Creek
4800 West Copans Rd.
Coconut Creek, FL 33063

RE: Public Participation Report
SOS Children's Village Site Plan
PZ-20120007

Dear Sirs,

The KEITH Team conducted a public participation outreach program for the site plan to modify the existing administration building at the SOS Children's Village. The following is a summary of the efforts and results.

- On January 22, 2021 a mailing was sent out to residents within 500 feet of the Village. The mailing list was prepared by the Broward County Property Appraiser. The notice included the nature of the project and arial map and the time and place of the meeting. The meeting was scheduled for February 8th at 7 PM at the location of the improvement which is adjacent to the notified property owners.
 - Attached is a copy of the notice.
 - List of property owners within 500 feet.
- On February 8th members of the KEITH Team were present along with the Executive Director of SOS to present the project which included renderings, site plans and landscape plans. There were no neighborhood attendees at the meeting, and we received no emails or phone calls for additional information.

Sincerely,

James Kahn, AICP



January 22nd, 2021

Dear Neighbor:

This letter is to inform you that The SOS Children's Village has submitted a site plan to the City of Coconut Creek for an addition to an existing building. The addition is to the administrative building located at 3681 NW 59 Place. The addition is one story and is 2,250 square feet. An aerial indicating the location of the addition is on the reverse side. There will be a meeting at the site to review the application and solicit comments.

If you are unable to attend and want to send comments or have questions, please send to:

James Kahn, AICP
954-788-3400 or email to:
jkahn@keithteam.com

SCHEDULE OF EVENTS

SOS Children Village Public Meeting:
Date: Monday, February 8th, 2021
Time: 7:00 PM - 8:00 PM
Location: SOS Children Village - Administrative Building
Address: 3681 NW 59th Place, Coconut Creek, FL 33073

Sincerely,

James Kahn, AICP

CC: City of Coconut Creek
SOS Children's Village



DRC SUBMITTAL PLAN SET FOR SOS CHILDREN'S VILLAGE

3681 NW 59th PLACE
COCONUT CREEK, FLORIDA 33073

FEMA FLOOD ZONE:

THE PROPERTY IS LOCATED WITHIN FLOOD ZONE X, AS SHOWN ON F.I.R.M. NUM. 12011C0166H, BEARING A MAP EFFECTIVE DATE OF 08/18/2014.

RELATIONSHIP BETWEEN NGVD 1929 AND NAVD 1988


DATUM	DIFFERENCE	ELEV.
NGVD 1929	+1.56 FEET	1.56'
NAVD 1988		0.00'

ALL ELEVATIONS SHOWN ON THESE PLANS ARE
BASED ON NAVD 1988 DATUM

LAND DESCRIPTION:

A PORTION OF PARCELS "B" AND "C", "MAPLE POND ~ SOS CHILDREN'S VILLAGE OF FLORIDA", ACCORDING TO THE PLAT THEREOF AS RECORDED IN PLAT BOOK 150, PAGE 05, OF THE PUBLIC RECORDS OF BROWARD COUNTY, FLORIDA.

PROJECT LOCATION



LOCATION MAP


SECTION 5, TOWNSHIP 48S, RANGE 42E
FOLIO #484205190030

INDEX OF SHEETS		
Sheet Sequence No.	Sheet Identification	Sheet Title
	--	COVER
1-2	--	PLAT
3	S1	SURVEY
4	SP-101	SITE PLAN
5	SP-102	SITE PLAN DETAILS
		CIVIL PLANS
6	GI-001	LEGEND
7	GI-002	GENERAL CONSTRUCTION NOTES
8	GI-003	CONSTRUCTION SPECIFICATIONS
9	CG-101	EROSION AND SEDIMENTATION CONTROL PLAN
10	CD-101	DEMOLITION PLAN
11	CP-101	ENGINEERING PLAN
12	CP-501	ENGINEERING DETAILS
		LANDSCAPE PLANS
13	LD-101	TREE DISPOSITION PLAN
14	LP-001	LANDSCAPE NOTE
15	LP-101	LANDSCAPE PLAN
16	LP-501	LANDSCAPE DETAILS
		ARCHITECTURAL PLANS
17	E1	FLOOR PLAN EXISTING
18	A1	FLOOR PLAN PROPOSED
19	A2	ELEVATIONS

THESE PLANS MAY HAVE BEEN
REDUCED IN SIZE BY REPRODUCTION.
THIS MUST BE CONSIDERED WHEN
OBTAINING SCALED DATA.



PREPARED FOR:
SEAWOOD BUILDERS
1324 W. NEWPORT CENTER DRIVE
DEERFIELD BEACH, FL 33442




THOMAS F. DONAHUE, P.E.
FLORIDA REG. NO. 60529
(FOR THE FIRM)

PROJECT No. 11204.00 DECEMBER, 2020


MAPLE POND - SOS CHILDREN'S VILLAGE OF FLORIDA

A PORTION OF THE NE 1/4 OF SECTION 8 AND THE SE 1/4 OF SECTION 5, TOWNSHIP 48 SOUTH, RANGE 42 EAST
 A REPLAT OF A PORTION OF TRACT I, BLOCK 87 AND TRACT 67, BLOCK 84, "PALM BEACH FARMS CO. PLAT NO. 3"
 PLAT BOOK 2, PAGES 45 - 54, PALM BEACH COUNTY RECORDS
 CITY OF COCONUT CREEK, BROWARD COUNTY, FLORIDA

PREPARED BY:
KEITH AND SCHNARS, P.A.
 ENGINEERS - PLANNERS - SURVEYORS
 6500 NORTH ANDREWS AVENUE
 FORT LAUDERDALE, FLORIDA 33309
 (305) 776-1616
 MARCH, 1990



"PALM BEACH FARMS CO. PLAT NO. 3"
(P.B. 2, PGS. 45-54, P.B.C.R.)



SURVEY NOTES

- ⊙ INDICATES SET PERMANENT REFERENCE MONUMENT.
- SURVEY DATA IN FIELD BOOK DF10.
- BEARINGS SHOWN HEREON ARE BASED ON THE "SAWGRASS EXPRESSWAY" RIGHT-OF-WAY MAP AS RECORDED IN MISCELLANEOUS RIGHT-OF-WAY MAP BOOK II, PAGE 36, BROWARD COUNTY RECORDS AND ARE ASSUMED.
- HHHHH INDICATES NON-VEHICULAR ACCESS LINE.
- BENCHMARK ELEVATIONS SHOWN HEREON ARE BASED ON THE NATIONAL GEODETIC VERTICAL DATUM OF 1929 AND WERE ESTABLISHED FROM BENCHMARKS SUPPLIED BY BROWARD COUNTY ENGINEERING DEPARTMENT (BENCHMARK 2430, ELEV. = 15.000') TOP OF STEEL POST FOR WATER GAUGE NO. 257,46.5' EAST OF LYONS ROAD CENTERLINE AND 30' NORTHWEST OF BUTLER ROAD CENTERLINE, IN CANAL.
- P.O.B. INDICATES POINT OF BEGINNING.

RESTRICTIONS

THIS PLAT IS HEREBY RESTRICTED AS FOLLOWS:
 PARCEL A - CONSERVATION, RECREATION, OPEN SPACE AND DRAINAGE PURPOSES.
 PARCEL B - RECREATION AND OPEN SPACE PURPOSES.
 PARCEL C - SPECIAL RESIDENTIAL FACILITY, CONTAINING 30 SLEEPING ROOMS (15 DWELLING UNIT EQUIVALENTS) AS DEFINED BY THE BROWARD COUNTY LAND USE PLAN.
 THIS NOTE IS REQUIRED BY CHAPTER 5, ARTICLE IX, BROWARD COUNTY CODE OF ORDINANCES, AND MAY BE AMENDED BY APPROVAL OF THE BROWARD COUNTY BOARD OF COUNTY COMMISSIONERS.

THE NOTATION AND ANY AMENDMENTS THERETO ARE SOLELY INDICATING THE APPROVED DEVELOPMENT LEVEL FOR PROPERTY LOCATED WITHIN THE PLAT AND DO NOT OPERATE AS A RESTRICTION IN FAVOR OF ANY PROPERTY OWNER INCLUDING AN OWNER OR OWNERS OF PROPERTY WITHIN THIS PLAT WHO TOOK TITLE TO THE PROPERTY WITH REFERENCE TO THIS PLAT.

NOTICE

THERE MAY BE ADDITIONAL RESTRICTIONS THAT ARE NOT RECORDED ON THIS PLAT THAT MAY BE FOUND IN THE PUBLIC RECORDS OF THIS COUNTY.

SURVEY NOTES CONT.

- A BLANKET EASEMENT FOR THE CONSTRUCTION, MAINTENANCE AND REPAIR OF THE UTILITY AND DRAINAGE FACILITIES EXISTS OVER THIS ENTIRE PLAT; HOWEVER, SAID EASEMENT IS NON-EXCLUSIVE AND SHALL NOT HAVE PRIORITY OVER ANY EXISTING OR FUTURE STRUCTURES, NOR DEEMED TO BE IN CONFLICT WITH ANY OTHER USE OF THESE LANDS SHOWN HEREON.
- THIS PLAT CONTAINS A LOCAL AREA OF PARTICULAR CONCERN AND HAS BEEN DESIGNATED BY THE BROWARD COUNTY BOARD OF COUNTY COMMISSIONERS AS ENVIRONMENTALLY SENSITIVE.
- DEVELOPMENT WITHIN THIS PLAT MUST BE CONSISTENT WITH THE MITIGATION RECOMMENDATIONS CONTAINED WITHIN THE "AGREEMENT BETWEEN BROWARD COUNTY AND FRIENDS OF SOS CHILDREN'S VILLAGE, INC. FOR COMPLIANCE WITH CONDITIONS OF ENVIRONMENTAL IMPACT REPORT," OR WITHIN AN AGREEMENT REQUIRED PURSUANT TO SECTION 5-198(I)(3), BROWARD COUNTY CODE OF ORDINANCES (REFR. OR. 16696, PG. 950, B.C.R.)
- THIS PLAT CONTAINS LAND THAT HAS BEEN DESIGNATED AS A NATURAL RESOURCE AREA BY THE BROWARD COUNTY BOARD OF COUNTY COMMISSIONERS. ANY CLEARING ACTIVITIES MUST BE IN COMPLIANCE WITH COUNTY ORDINANCE 89-6.

AREA TABULATION

PARCEL "A"	312,292 SQ. FT., 7.17 ACRES
PARCEL "B"	162,594 SQ. FT., 3.73 ACRES
PARCEL "C"	351,897 SQ. FT., 8.08 ACRES
TOTAL	826,783 SQ. FT., 18.98 ACRES

CURVE TABLE

NAME	DELTA	RADIUS	LENGTH
CV-1	049°59'41"	25.00'	21.81'
CV-2	110°35'41"	45.00'	86.86'
CV-3	049°59'41"	25.00'	21.81'
CV-4	049°59'41"	25.00'	21.81'
CV-5	089°23'04"	45.00'	70.20'
CV-6	049°59'41"	25.00'	21.81'
CV-7	021°38'03"	832.54'	314.36'
CV-8	021°38'03"	872.54'	329.46'
CV-9	102°36'38"	30.00'	53.73'
CV-10	102°36'38"	70.00'	125.36'
CV-11	021°38'03"	852.54'	321.91'
CV-12	102°36'38"	50.00'	89.54'

A C R E A G E

CONSTRUCTION SPECIFICATIONS

Section 20 - General Specifications Paving Grading Drainage and Earthwork

20. General
20.1. It is the intent of these specifications to describe the minimum acceptable technical requirements for the materials and workmanship for construction of site improvements for this project. Such improvements may generally include, but not to be limited to, clearing, grading, paving, removal of existing pavement storm drainage, water lines and sanitary sewers.
20.2. It is the intent that the Florida Department of Transportation (FDOT) "Standard Specifications for Road and Bridge Construction: (current edition) together with "Supplemental Specifications to the Standard Specifications for Road and Bridge Construction" (current edition), and the FDOT Roadway and Traffic Design Standards (current edition) be used where applicable for the various work, and that where such wording therein refers to the State of Florida and its Department of Transportation and personnel, such wording is intended to be replaced with the wording which would provide proper terminology; thereby making such "Standard Specifications for Road and Bridge Construction" together with the FDOT Roadway and Traffic Design Standards as the "Standard Specifications" for this project. If within a particular section, another section, article or paragraph is referred to, it shall be part of the Standard Specifications also. The Contractor shall abide by all local and State laws, regulations and building codes which have jurisdiction in the area.
20.3. The Contractor shall furnish all labor, materials and equipment and perform all operations required to complete the construction of a paving and drainage system as shown on the plans, specified herein, or both. It is the intent to provide a complete and operating facility in accordance with these specifications and the construction drawings. The material and equipment shown or specified shall not be taken to exclude any other incidentals necessary to complete the work.
20.4. All labor, materials, and methods of construction shall be in strict accordance with the plans and construction specifications and the minimum engineering and construction standards adopted by the unit of government which has jurisdiction and responsibility for the construction. Where conflicts or omissions exist, the jurisdictional government Engineering Department's standards shall govern. Substitutions and deviations from plans and specifications shall be permitted only when written approval has been issued by the Engineer.
20.5. Guarantee - all materials and equipment to be furnished and/or installed by the Contractor under this contract, shall be guaranteed for a period of (1) one year from the date of final acceptance thereof, against defective materials, design and workmanship. Upon receipt of notice from the owner of failure of any part of the guaranteed equipment or materials, during the guarantee period, the affected part or materials shall be replaced promptly with new parts or materials by the contractor, at no expense to the owner. In the event the Contractor fails to make necessary replacement or repairs within (7) seven days after notification by the owner, the owner may accomplish the work at the expense of the contractor.
21. Earthwork
21.1. All areas within the project limits shall be cleared and grubbed prior to construction. This shall consist of the complete removal and disposal of all trees, brush, stumps, roots, grass, weeds, rubbish and all other obstructions resting on or protruding through the surface of the existing ground to a depth of 1'. All work shall be in accordance with section 110 of the Standard Specifications.
21.2. None of the existing limerock material from demolished pavement is to be incorporated in the new limerock base, unless noted in plans. The existing limerock material from demolished pavement may be incorporated into the stabilized subgrade / subbase, or stabilized shoulder.
21.3. Fill material shall be classified as A-1, A-3, or A-2-4 in accordance with AASHTO N-145 and shall be free from vegetation and organic material. Not more than 12% by weight of fill material shall pass the no. 200 sieve.
21.4. All fill material in areas not to be paved shall be compacted to 95% of the maximum density as determined by AASHTO T-99.
21.5. All material of construction shall be subject to inspection and testing to establish conformance with the specifications and suitably for the uses intended. The Contractor shall notify the Engineer at least 24 hours prior to the time he will be ready for an inspection or test. The Contractor shall follow City and County inspection procedures. The Contractor shall not proceed with any phase of work dependent on an inspection or test of an earlier phase of work, prior to that test or inspection passing. The Contractor shall be responsible for providing certified material test results to the Engineer of record prior to the release of final certification by the Engineer. Test results must include, but may not be limited to, densities for subgrade and limerock, utilities, excavation, asphalt gradation reports, concrete cylinders, etc.
21.6. When encountered, muck shall be completely removed from the center line (10) ten feet beyond the edge of pavement each side. All such material shall be replaced by approved granular fill.
21.7. When encountered within drainage swales, hardpan shall be removed to full depth for a width of (5) five feet at the invert and replaced with granular materials.
21.8. All underground utilities and drainage installations shall be in place prior to subgrade compaction and pavement construction.
21.9. Ground adjacent to roadway/pavement having runoff shall be graded (2) two inches lower than the edge of pavement to allow for the placement of sod.
21.10. Site grading elevations shall be within 0.1' of the required elevation for non paved areas and all areas shall be graded to drain without ponding.
21.11. The Contractor shall perform all excavation, fill, embankment and grading to achieve the proposed plan grades including typical road sections, side slopes and canal sections. All work shall be in accordance with section 120 of the Standard Specifications. If fill material is required in excess of that generated by the excavation, the Contractor shall supply this material as required from off-site.
21.12. A 2" blanket of top soil shall be placed over all areas to be sodded or seeded and mulched within the project limits unless otherwise indicated on the plans.
21.13. Sod shall be St. Augustine unless otherwise indicated on the plans, and shall be placed on the graded top soil and watered to insure satisfactory condition upon final acceptance of the project.
22. Drainage
22.1. Inlets - all inlets shall be the type designated on the plans, and shall be constructed in accordance with section 425 of the Standard Specifications. All inlets and pipe shall be protected during construction to prevent siltation in the drainage systems by way of temporary plugs and plywood or plastic covers over the inlets. The entire drainage system shall be cleaned of all debris prior to final acceptance.
22.2. Pipe specifications: the material type is shown on the drawings by one of the following designations:
- RCP = reinforced concrete pipe, ASTM designation C-76, section 941 of the Standard Specifications.
- CMP = corrugated metal (aluminum) pipe, ASTM designation M-196.
- CMP (smooth lined) = corrugated metal aluminum pipe, (smooth lined) ASTM

designations M-196.
- SCP = slotted concrete pipe, sections 941 and 942, of the Standard Specifications.
- PVC = polyvinyl chloride pipe.
- PCMP = perforated cmp, section 945, of the Standard Specifications
- Corrugated High Density Polyethylene Pipe (HDPE) (12 Inches to 60 Inches), shall meet the requirements of FDOT Specification section 948-2.3.
22.3. Pipe backfill - requirements for pipe backfill crossing roads or parking areas shall be as defined in the section 125-8, of the Standard Specifications. Pipeline backfill shall be placed in 6 inch lifts and compacted to 100% of the standard proctor (AASHTO T-99 specifications)
22.4. Location of drainage structures shall govern, and pipe length may have to be adjusted to accomplish construction as shown on these plans.
22.5. Distance and lengths shown on plans and profile drawings are referenced to the inner walls of structures.
22.6. Filter fabric shall be Mirafi, Typar or equal conforming to section 985 of the Standard Specifications.
23. Asphalt Paving
23.1. Where new asphalt meets existing asphalt, the existing asphalt shall be saw cut to provide a straight even line. Prior to removing curb or gutter, the adjacent asphalt shall be saw cut to provide a straight even line.
23.2. Internal asphalt paving constructed on existing sandy soils shall be constructed with a 12' subgrade, compacted to a minimum density of 100% maximum density as determined by AASHTO T-99. The compacted subgrade shall be constructed in the limits shown on the plans. All subgrade shall have an LBR of 40 unless otherwise noted.
23.3. Asphaltic concrete surface course shall be constructed to the limits shown on the plans. The surface course shall consist of the thickness and type asphaltic concrete as specified in the plans. All asphaltic concrete shall be in accordance with sections 320, 327, 330, 334, 336, 337, 337, 338, 339 and 341 of the Standard Specifications.
23.4. Limerock base shall be prepared, compacted and graded and shall be in accordance with section 200 of the Standard Specifications. All limerock shall be compacted to 98% per AASHTO T-180 and have not less than 70% of carbonates of calcium and magnesium unless otherwise designated. The Engineer shall inspect the completed base course and the Contractor shall correct any deficiencies and clean the base course prior to the placement of the prime coat. A tack coat will also be required if the Engineer finds that the primed base has become excessively dirty or the prime coat has cured to the extent of losing bonding effect prior to placement of the asphaltic concrete surface course. The prime and tack coats shall be in accordance with section 300 of the Standard Specifications.
23.5. Limerock base material shall be placed in maximum 6" lifts. Bases greater than 6" shall be placed in two equal lifts. If, through field tests, the Contractor can demonstrate that the compaction equipment can achieve density for the full depth of a thicker lift, and if approved by the engineer, the base may be constructed in successive courses of not more than 8 inches (200 mm) compacted thickness.
23.6. Asphalt edges that are not curbed shall be saw cut to provide a straight even line to the dimensions shown on plans.
24. Concrete Construction
24.1. Concrete sidewalk shall be in accordance with section 522 of the Standard Specifications and in accordance with F.D.O.T. Roadway and Traffic Design Standards, index no. 310. Concrete sidewalk shall be 4" thick, unless otherwise noted and constructed on compacted subgrade, with 1/2" expansion joints placed at a maximum of 75', unless otherwise noted on plans. Crack control joints shall be 5' on center. All concrete sidewalks that cross driveways shall be 6" thick, unless otherwise noted on plans.
24.2. Sidewalk Curb ramps shall be in accordance with F.D.O.T. Roadway and Traffic Design Standards, index no. 304.
24.3. Concrete curb shall be constructed to the limits shown on the plans. The concrete shall have a minimum compressive strength of 2500 PSI at 28 days and shall be in accordance with section 520 of the Standard Specifications. Concrete curbing shall be in accordance with F.D.O.T. Roadway and Traffic Design Standards, index no. 300.
24.4.

Section 30 - Water distribution and sanitary sewer force mains.

30. Materials:
Note: If materials list here on are in conflict with utility owner, material owner requirements shall govern.
30.1. All water main pipe, including fittings, shall be color coded or marked using blue as a predominant color to differentiate drinking water from reclaimed or other water. Underground plastic pipe shall be solid-wall blue pipe, shall have a co-extruded blue external skin, or shall be white or black pipe with blue stripes incorporated into, or applied to, the pipe wall; and underground metal or concrete pipe shall have blue stripes applied to the pipe wall. Pipe striped during manufacturing of the pipe shall have continuous stripes that run parallel to the axis of the pipe, that are located at no greater than 90-degree intervals around the pipe, and that will remain intact during and after installation of the pipe. If tape or paint is used to stripe pipe during installation of the pipe, the tape or paint shall be applied in a continuous line that runs parallel to the axis of the pipe and that is located along the top of the pipe; for pipes with an internal diameter of 24 inches or greater, tape or paint shall be applied in continuous lines along each side of the pipe as well as along the top of the pipe.
30.2. Ductile iron pipe for water distribution mains shall conform to ANSI/AWWA standard C151/A21.51 latest revision, "ductile iron pipe centrifugally cast in metal molds or sand-lined molds" with a minimum wall thickness of class 51 (pressure class 350) unless otherwise noted in the plans. Ductile iron pipe shall be cement lined and seal coated in accordance with ANSI/AWWA standard C104/A21.4 latest revision. The pipe shall be adapted for use with class 250 fittings for all sizes. Water main shall be colored blue in accordance with Florida State Statutes.
30.3. Ductile iron pipe for sewage force mains shall conform to ANSI/AWWA standard C151/A21.51 latest revision, "ductile iron pipe centrifugally cast in metal molds or sand-lined molds" with a minimum wall thickness of class 51 (pressure class 350) unless otherwise noted in the plans. Ductile iron pipe shall be interior ceramic epoxy lined and exterior coated with the manufacturer's coating system (Protecto 401 ceramic epoxy with a minimum dry film thickness of 40 mils and an outside coating of either coal tar epoxy or asphalt). Cement mortared linings are not appropriate for this application.
30.4. All pipe & fittings on the lift station sites shall be ductile iron conforming to the same specifications as above for sewage force mains except that flanged ductile iron pipe & fittings shall be used inside valve pits and wet wells. Flanged pipe and fittings shall conform to ANSI/AWWA C115/a21.15 latest revision and ANSI/AWWA C110/A21.10 latest revision. The following thickness classes shall be adhered to: 4" - 12" - class 52, 14" & larger - class 51.
30.5. PVC pressure pipe for sizes 4" through 12" and shall conform to ANSI/AWWA standard C900 latest revision. PVC pressure pipe shall be made from class 12454-a or class 12454-b virgin material and conform with the outside diameter of cast iron pipe with a minimum wall thickness of dr series 18. Ultra violet degradation or sun bleached pipe will be cause for rejection. Water main shall be colored blue in accordance with

Florida State Statutes. Force main shall be impregnated with green pigment. Reuse main shall be impregnated with purple pigment.
30.6. Ductile iron fittings for water distribution mains shall conform to ANSI/AWWA standard C110/A21.10 latest revision. Fittings 4" and larger shall be cement lined and seal coated in accordance with ANSI/AWWA standard C104/A21.4 latest revision. Water Main fitting shall be colored blue in accordance with Florida state statutes.
30.7. Cast iron and ductile iron fittings for sewage force mains shall conform to ANSI/AWWA standard C110/A21.10 latest revision. Fittings 4" and larger shall be coated in accordance with the requirements of ductile iron pipe for sewage force mains.
30.8. Joints for bell and spigot ductile iron pipe and fittings shall conform to ANSI/AWWA standard C111/A21.11 latest revision. Mechanical joint or push-on joint to be rubber gasket compression-type. Special fittings and joints shall be considered for specific installation subject to the approval of the engineer.
30.9. Joints for PVC pressure pipe shall be bell and spigot push-on rubber gasket type only. No solvent weld or threaded joints will be permitted.
30.10. Water distribution system restraint: all fittings and specific pipe joints shall be restrained as outlined below:
- Joint restraint
- Push-on P.V.C. EBAA iron series 1600
- Push-on DIP EBAA iron series 1700
- tr-flex by U.S. Pipe or
- flex ring by American
- Fittings w/ DIP EBAA iron series 1100 megalug
- Fittings w/ P.V.C. EBAA iron series 2000 megalug
- Length of restrained pipe shall be as indicated on restrained joint pipe detail. (see water & sewer detail sheet)
30.11. Sewage force main system restraint: all fittings and specific pipe joints shall be restrained as outlined below
- Joint restraint
- Push-on P.V.C. EBAA iron series 1600
- Push-on DIP EBAA iron series 1700
- tr-flex by U.S. Pipe or
- flex ring by American
- Fittings w/ DIP EBAA iron series 1100 megalug
- Fittings w/ P.V.C. EBAA iron series 2000 megalug
- Length of restrained pipe shall be as indicated on restrained joint pipe detail. (see water & sewer detail sheet)
30.12. Water distribution valves shall be gate valves, iron body, fully resilient seat bronzed mounted non-rising stem, rated at 200 PSI and conforming to ANSI/AWWA C509 latest revision, and shall have mechanical joints.
30.12.1. Gate valves 4" and larger shall be Mueller A-2360, American 250 line or Clow F-6100, conforming to ANSI/AWWA C500 latest revision or approved equal.
30.12.2. Tapping valves shall be Mueller T-2360 or approved equal.
30.12.3. Gate valves 3" or less shall be Nibco T-133 or T-136 with malleable hand wheels or approved equal.
30.13. Tapping sleeves shall be Mueller H615, Clow F-2505 or approved equal.
30.14. Valve boxes shall be U.S. foundry 7500 or approved equal painted blue with the designation "water".
30.15. Retainer glands for DIP shall conform to ANSI/AWWA C111/A21.11 latest revision. All glands shall be manufactured from ductile iron as listed by underwriters laboratories for 250 psi minimum water pressure rating. Clow corporation model F-1058, standard fire protection equipment company or approved equal.
30.16. Dresser couplings shall be regular black couplings with plain gaskets for galvanized steel pipe. They shall be dresser style 90. No substitutions allowed.
30.17. Fire hydrants shall be Mueller centurion traffic type A-423 with 5 1/4" internal valve opening or approved equal. Pumper nozzle to be 18" from finished grade. All hydrants to be installed with control valve. Retainer glands are preferred for restraining. Fire hydrant shall comply with ANSI/AWWA C502 latest revision. Fire hydrants shall be painted in accordance with NFPA #291 or per agency standards having jurisdiction. Blue raised reflective pavement marker (rpm) shall be used to identify fire hydrant location. The placement of the rpm to be at the centerline of the outside roadway lane.
30.18. Sewage force main valves shall be plug valves which shall be of the non-lubricated, eccentric type with resilient faced plugs, port areas for valves 20 inches and smaller shall be at least 80% of full pipe area. Port area of valves 24 inches and larger shall be at least 70% of full pipe area. The body shall be of semi-steel (ASTM A-126 C1.b) and shall have bolted bonnet which gives access to the internals of the valve. Seats shall be welded overlay of high nickel content or a stainless steel plate locked in the body cavity. If a plate is used, it shall be replaceable through the bonnet access. Bearings shall be permanently lubricated of stainless steel, bronze or Teflon lined, fiber glass backed Duralon. Bearing areas shall be isolated from the flow with grit seals. Valves shall have packing bonnets where the shaft protrudes from the valve and the packing shall be self-adjusting chevron type which can be replaced without removing the bonnet. All nuts, bolts, springs and washers shall be stainless steel.
30.19. Plug valves shall be designed for a working pressure of 150 PSI the valve and actuator shall be capable of satisfactory operation in either direction of flow against pressure drops up to and including 100 PSI (for plug valves over 12 in diameter). Valves shall be bubble tight in both directions at 100 psi differential. Plug valves over 12" in diameter shall have worm gear operators. The operating mechanism shall be for buried service with a 2 inch square operating nut.
30.20. Plug valves are to be installed with the seat pointed towards the upstream flow, when specified.
30.21. Swing check valves for water, sewage, sludge, and general service shall be of the outside lever and spring or weight type, in accordance with ANSI/AWWA C 508 latest revision swing-check valves for waterworks service, 2 through 24 NPS, unless otherwise indicated, with full-opening passages, designed for a water-working pressure of 150 PSI they shall have a flanged cover piece to provide access to the disc.
30.22. High density polyethylene pipe (HDPE) for water distribution mains shall conform to AWWA C906 standard, latest revision. Pipes shall be color-coded blue, minimum 40 feet standard lengths.
31. Service connection:
31.1. Service saddles shall be fusion bonded plastic coated ductile iron (ASTM A536) with stainless steel straps, saddles shall be double strap type.
31.2. Service lines shall be polyethylene (PE 3408), 200 p.s.i rated, DR9. Pipe joints shall be of the compression type totally confined grip seal and coupling nut.
31.3. Corporation stops shall be manufactured of brass alloy in accordance with ASTM B-62 with threaded ends, as manufactured by Ford ballcorp, catalog # 1100 or approved equal.
31.4. Curb stops shall be Ford v63-44w-x" latest revision or approved equal.
31.5. Meter stops shall be 90 degree locking type and shall be of bronze construction in accordance FV63-777W" latest revision with ASTM B-62. Meter stops shall be closed bottom design and resilient "O" ring sealed against external leakage at the top. Stops

shall be equipped with a meter coupling nut on the outlet sides, as manufactured by Ford or approved equal.
32. Installation:
32.1. Where restrained pipe joints are required due to fittings, appurtenances, etc., pipe material shall be DIP
32.2. All PVC pipe shall be installed in accordance with the uni-bell plastic pipe association "guide for installation of PVC pressure pipe for municipal water distribution system," and ANSI/AWWA C605-xx latest revision standard.
32.3. All DIP shall be installed in accordance with ANSI/ C600-xx latest revision.
32.4. All water mains shall typically be laid with a minimum 36" cover for PVC and 30" cover for DIP.
32.5. Detector tape shall be laid 18 inches above all water and sewer lines. A 14 gauge multi-strand wire shall be attached to all nonconductive water mains to facilitate location. An extra 4 feet of wire shall be provided at all valves, blow-offs, hydrants, etc. The wire shall be tested for continuity at the pressure test.
32.6. Pipe deflection shall not exceed 50% of the maximum deflection recommended by the manufacturer.
32.7. A continuous and uniform bedding shall be provided. Backfill material shall be placed in accordance with the plans and specifications.
32.8. All valves shall be installed with adjustable cast iron valve boxes with the word "water" or "sewer", as applicable, cast in the cover. U.S. foundry or approved equal.
33. Testing:
33.1. Before any physical connections and acceptance for operation to the existing water mains are made, the complete water system shall be flushed, pressure tested and disinfected. Copies of passing bacteriological results and pressure test results must be submitted to, and approved by, the engineer, utility owner, and health department. Hydrostatic testing of new mains shall be performed at a minimum starting pressure of 150 PSI for two hours in accordance with ANSI/AWWA C600-05 (hydrostatic test). The pressure test shall not vary more than 5 PSI during the test. The allowable leakage during the pressure test shall be less than the number of gallons per hour as determined by the formula:
L = (sdf(p1/2)/148,000.
In which L equals the allowable leakage in gallons per hour. S equals length of pipe (linear feet), d equals nominal diameter of pipe (inches) and p equals the average test pressure (pounds per square inch gauge). Maximum length of test pipe section should be 2000 feet. The water system shall be disinfected in accordance with the ANSI/AWWA C651-05 (water main bacteriological tests).
33.2. The pressure test shall be witnessed by a representative of the utility owner and the engineer of record.
33.3. For water distribution pipes, sampling points shall be provided by the contractor at the locations shown on the plans.
33.4. For water distribution pipes, disinfection and bacteriological testing shall be in accordance with ANSI/AWWA C651-14 (water main bacteriological tests). Maximum distance between sampling points shall be as follows:
- Transmission mains: every 1200 feet
- Branch mains: every 1000 feet
- Isolated mains < 1000 feet: 2 sample points
- Isolated mains > 1000 feet: 3 sample points

Section 40 - Gravity Sanitary Sewer Collection System

40. General:
40.1. Manhole, valve box, meter box and other structure rim elevations within the limits of construction are to be adjusted to conform to plan grades proposed in these plans. If no other individual cost item is included in the contract schedule for a particular structure adjustment.
40.2. Distance and lengths shown on plans and profile drawings are referenced to the center of structures.
41. Materials:
Note: If materials list here on are in conflict with utility owner, material owner requirements shall govern.
41.1. All PVC sewer pipe and fittings shall be non-pressure polyvinyl chloride (PVC) pipe conforming to ASTM D 3034, SDR 26, with push-on rubber gasket joints.
41.2. Ductile iron pipe shall conform to ANSI/AWWA C151/A21.51-xx latest revision, "ductile iron pipe centrifugally cast in metal molds or sand-lined molds" with wall thickness class 51 for 8" and above, class 52 for 4" and 6", unless otherwise directed by the engineer. Ductile iron pipe shall be epoxy lined or coated with the manufacturer's coating system as approved by the engineer of record and the local municipality or utility owner. In either case, the engineer's review and approval is required for either alternative prior to construction. Cement mortared linings are not appropriate for this application.
41.3. All ductile iron fittings shall conform to ANSI/AWWA standard C110/A21.10-xx latest revision. All fittings and accessories shall be epoxy lined and as manufactured or supplied by the pipe manufacturer or approved equal.
41.4. Manholes shall be precast per ASTM C 478 and in accordance with the plans and specifications.
41.5. Manholes are to be sealed with type II sulphate resistant cement or approved equal - no molding plaster.
41.6. Joints for bell and spigot ductile iron pipe and fittings shall conform to ANSI/AWWA standard C111/A21.11-xx latest revision. Mechanical joint or push-on joint to be rubber gasket compression- type.
41.7. PVC clean-outs to have screw type access plug. Long radius wye connections and fittings shall be used in order to access clean-out operations.
41.8. Cleanouts shall be installed at all sewer services exceeding 75' in length (every 75') with a clean out at the property line, easement line, or 5' from a building. The contractor shall coordinate the location of the building cleanout (5' from the building) and elevation of the end of the sewer service with the building plumbing contractor. Cleanouts shall be the same size as the service lateral in which they are installed.
42. Installation:
42.1. PVC sewer pipe shall be laid in accordance with ASTM D 2321 and the Uni-Bell plastic pipe association's "recommended practice for the installation of PVC sewer pipe."
42.2. DIP shall be installed in accordance with ANSI/AWWA C-600-xx latest revision.
42.3. Pipe to manhole connection to be Fernco neoprene boot couplings with stainless steel accessories or approved equal.
42.4. Manholes shall be set plumb to line and grade on firm subgrade providing uniform bearing under the base.
42.5. All openings and joints shall be sealed watertight.
42.6. Two coats of Koppers 300-m, first red, second one black, shall be applied to the inside of all manholes and shall be applied in accordance with the manufacturer's specifications (16 mils per coat). Coating as required by utility owner or engineer shall be applied to the outside of the manhole. The interior coats shall be applied after sewer

lampp of lines. After the application of each coat, the utility owner and engineer shall inspect the manholes. The inspection shall be scheduled a minimum of 48 hours prior to inspection.
43. Testing: Testing of gravity sewer mains and laterals shall be in accordance with the utility owner's minimum design and construction standards latest revision.
43.1. After construction of the sewer system, the engineer may require a visual infiltration and/or exfiltration test to be performed on the entire system or any part thereof.
43.2. An air test may be substituted for the water exfiltration test, upon approval of the engineer.
43.3. The allowable limits of sewer pipe leakage for gravity sewer mains shall not exceed 100 gallons per inch of inside pipe diameter per mile per day for any section tested. No visible leakage shall be allowed.
43.4. The installed sewers may require video inspections.



301 East Atlantic Blvd. Pompano Beach, FL 33060 PH: (954) 788-3400

Florida Certificate of Authorization: 7928 Licensed Business Number: 6860

Table with 3 columns: NO., DESCRIPTION, DATE. Title: REVISIONS

PRELIMINARY PLAN NOT FOR CONSTRUCTION THESE PLANS ARE NOT FULLY PERMITTED AND ARE SUBJECT TO REVISIONS MADE DURING THE PERMITTING PROCESS. RESPONSIBILITY FOR THE USE OF THESE PLANS PRIOR TO OBTAINING PERMITS FROM ALL AGENCIES HAVING JURISDICTION OVER THE PROJECT WILL FALL SOLELY UPON THE USER.

Table with 2 columns: ISSUE DATE, DESIGNED BY, DRAWN BY, CHECKED BY, BID-CONTRACT. Values: 12/15/2020, AM, AM, MG

THOMAS F. DONAHUE, P.E. FLORIDA REG. NO. 60529 (FOR THE FIRM)

CLIENT SEAWOOD BUILDERS

PROJECT SOS CHILDREN'S VILLAGE

SHEET TITLE CONSTRUCTION SPECIFICATIONS

Table with 2 columns: SHEET NUMBER, PROJECT NUMBER. Values: GI-003, 11204.00

REVISIONS		
NO.	DESCRIPTION	DATE

**PRELIMINARY PLAN
NOT FOR CONSTRUCTION**
THESE PLANS ARE NOT FULLY PERMITTED AND ARE SUBJECT TO REVISIONS MADE DURING THE PERMITTING PROCESS. RESPONSIBILITY FOR THE USE OF THESE PLANS PRIOR TO OBTAINING PERMITS FROM ALL AGENCIES HAVING JURISDICTION OVER THE PROJECT WILL FALL SOLELY UPON THE USER.

ISSUE DATE: 12/15/2020

DESIGNED BY: AS, SL

DRAWN BY: AS, SL

CHECKED BY: KS, MP

BID-CONTRACT:

MICHAEL J. PHILLIPS, R.L.A.
FLORIDA REG. NO. LA0001540
(FOR THE FIRM)

CLIENT

SEAWOOD BUILDERS

PROJECT

SOS CHILDREN'S VILLAGE


SHEET TITLE

LANDSCAPE DETAILS


SHEET NUMBER LP-501

PROJECT NUMBER 11204.00


Plotted by: asaton on Wednesday, September 23, 2020 9:40:08 AM STATUS: PRELIMINARY




11 TYPICAL SHRUB OFFSET AT BUILDING / CURB
PLAN NOT TO SCALE




08 SABAL PALM PLANTING DETAIL
SECTION NOT TO SCALE



06 ROOT BARRIER DETAIL
PLAN / SECTION NOT TO SCALE




03 SINGLE TRUNK TREE PLANTING DETAIL
SECTION NOT TO SCALE




NOTE: PLANT MATERIAL SHALL NOT BE PRUNED PRIOR TO INSTALLATION. AFTER PLANTS HAVE BEEN INSTALLED, EACH PLANT SHALL BE PRUNED FOR UNIFORMITY OR AT THE DIRECTION OF THE LANDSCAPE ARCHITECT. CONTRACTOR SHALL ASSURE PERCOLATION OF ALL PLANTING BEDS PRIOR TO INSTALLATION.


10 SHRUB AND GROUND COVER PLANTING
SECTION NOT TO SCALE




07 LARGE TREE PALM PLANTING DETAIL
SECTION NOT TO SCALE




05 SMALL / MEDIUM TREE PALM PLANTING DETAIL
SECTION NOT TO SCALE



04 MULTI-TRUNK TREE PLANTING DETAIL
SECTION NOT TO SCALE




02 FIRE HYDRANT CLEAR ZONE
PLAN NOT TO SCALE




01 TYPICAL SCREEN FOR UTILITIES / MECH. EQUIP.
PLAN / SECTION NOT TO SCALE

NOTE: REF. LP-201, LANDSCAPE NOTES, FOR ADDITIONAL REQUIREMENTS. ROOT BALL SIZE FOR ALL TREES AND PALMS TO BE IN PROPORTION TO SIZE AND TYPE OF PALM PER FLORIDA GRADES AND STANDARDS FOR NURSERY PLANTS.



09 SHRUB AND GROUND COVER PLANTING
PLAN NOT TO SCALE



REVISIONS
DATE: 12-08-20
01/29-21

ADDITION TO ADMINISTRATIVE OFFICES
FOR
SOS CHILDREN'S VILLAGES
3681 N.W. 59 PLACE, COCONUT CREEK, FLORIDA

MS ARCHITECTS, INC.
ARCHITECTS, PLANNERS
MIGUEL F. SANCHEZ
LIC. # AR 7456, AA 0001695
901 S. FEDERAL HWY., SUITE 200
FORT LAUDERDALE, FLORIDA 33316
(954) 463-3096
JOB NUMBER: 19-08-77

A-1
SHEET:
OF: 2

AREA CALCULATIONS:	
EXISTING OFFICE AREA	1,820 SQ. FT.
PROPOSED NEW OFFICE AREA	2,308 SQ. FT.
TOTAL OFFICE AREA (A/C)	4,128 SQ. FT.
EXISTING GARAGE	432 SQ. FT.
TOTAL ENCLOSED BUILDING AREA	4,560 SQ. FT.
EXISTING COVERED ENTRY	165 SQ. FT.
PROPOSED NEW COVERED ENTRY	35 SQ. FT.
TOTAL BUILDING COVERAGE	4,760 SQ. FT.

FLOOR PLAN
SCALE: 3/16" = 1'-0"

DRAWING NAME: Z:\A-Offices\SOS Childrens Villages\Construction drawings\DRG\EX-1A-1.dwg, 1/29/2021 9:01:23 AM, DWG To PDF.pcl

